



## QMFZ2.E235269 Plastics - Component

For enhanced search functionality, please visit UL's iQ™ Family of Databases.  
Click on a product designation for complete information.

[Page Bottom](#)

## Plastics - Component

[See General Information for Plastics - Component](#)

**NAN YA PLASTICS (HUI ZHOU) CORP LTD**

E235269

YONGSHI DA DAO

SHI WAN TOWN

HUIZHOU, GUANGDONG 516000 CHINA

									H	D	
		Min.		H	H	R T I			V	4	C
		Thk	Flame	W	A	Elec	Mech		T	9	T
Material Dsg	Color	mm	Class	I	I		Imp	Str	R	5	I
<b>Acrylonitrile Butadiene Styrene/Polybutylene Terephthalate (ABS/PBT), furnished as pellets.</b>											
1602	ALL	1.5	HB	-	-	60	60	60	-	-	-
<b>Acrylonitrile Butadiene Styrene/Polycarbonate (ABS/PC), furnished as pellets.</b>											
5612	ALL	1.5	HB	-	-	60	60	60	2	7	2
		3.0	HB	3	0	60	60	60			
5712(f1)	ALL	1.5	V-0	2	1	100	85	90	1	6	2
		3.0	V-0	1	0	100	85	90			
571P	ALL	1.5	V-0	-	-	60	60	60	-	-	-
		3.3	V-0	-	-	60	60	60			
571PG(e)	ALL	1.5-1.65	V-0	-	-	60	60	60	-	-	-
5722(f2)	ALL	1.5	V-0	3	0	100	90	100	3	7	0
		3.2	V-0	2	0	100	90	100			
<b>Polyamide 6 (PA6), furnished as pellets.</b>											
2110	ALL	0.75	V-2	4	0	140	75	75	0	5	0
		1.5	V-2	3	0	140	80	85			
		3.0	V-2	3	0	140	80	85			
2200M6	ALL	0.75	HB	-	-	65	65	65	0	5	0
		3.0	HB	1	0	65	65	65			
2200M9	ALL	1.5	HB	-	-	65	65	65	-	-	-
2210G(c)	ALL	0.75	HB	4	0	120	75	75	0	6	0
		1.5	HB	3	0	120	80	85			
		3.0	HB	3	0	120	80	85			
2210G2	ALL	0.75	HB	4	0	130	75	75	0	6	0
		1.5	HB	3	0	130	80	85			

		3.0	HB	3	0	130	80	85			
<b>2210G3</b>	ALL	0.75	HB	3	0	130	100	115	0	6	0
		1.5	HB	0	0	130	110	120			
		3.0	HB	0	0	130	110	120			
<b>2210G4</b>	ALL	0.75	HB	4	0	120	100	115	0	6	0
		1.5	HB	3	0	120	100	115			
		3.0	HB	0	0	120	100	115			
<b>2210G5</b>	ALL	0.75	HB	4	0	120	100	115	0	6	0
		1.5	HB	3	0	120	100	115			
		3.0	HB	0	0	120	100	115			
<b>2210G6</b>	ALL	0.75	HB	4	0	120	100	115	0	6	0
		1.5	HB	2	0	120	100	115			
		3.0	HB	0	0	120	100	115			
<b>2210G7</b>	ALL	0.75	HB	4	0	120	100	115	0	6	0
		1.5	HB	3	0	120	100	115			
		3.0	HB	3	0	120	100	115			
<b>2210G8</b>	ALL	0.75	HB	4	0	120	100	115	0	6	0
		1.5	HB	3	0	120	100	115			
		3.0	HB	3	0	120	100	115			
<b>2210G9</b>	ALL	0.75	HB	3	0	120	100	115	0	6	0
		1.5	HB	1	0	120	100	115			
		3.0	HB	0	0	120	100	115			
<b>2310</b>	ALL	0.75	V-0	4	0	140	90	110	0	6	0
		1.5	V-0	3	0	140	100	115			
		3.0	V-0	2	0	140	100	115			
<b>Polyamide 66 (PA66), with glass fiber reinforced, furnished as pellets.</b>											
<b>640PG(k)</b>	ALL	0.75	V-0	0	0	115	95	95	2	6	1
		3.0	V-0	0	0	115	95	95			
<b>640PG1</b>	ALL	0.75	V-0	0	0	115	95	95	2	5	1
		3.0	V-0	0	0	115	95	95			
<b>640PG8</b>	ALL	0.75	V-0	0	0	120	110	110	2	6	0
		3.0	V-0	0	0	120	110	110			
<b>641PG(k)</b>	ALL	3.0-3.3	V-0	0	0	65	65	65	2	5	0
<b>Polyamide 66 (PA66), furnished as pellets.</b>											
<b>6110</b>	ALL	0.75	V-2	4	0	130	80	85	0	6	0
		1.5	V-2	3	0	130	80	85			
		3.0	V-2	2	0	130	85	85			
<b>6210G(c)</b>	ALL	0.75	HB	4	0	105	80	85	0	6	0
		1.5	HB	2	0	105	80	85			
		3.0	HB	0	0	105	85	85			
<b>6210G2</b>	ALL	0.75	HB	4	0	120	80	85	0	6	0
		1.5	HB	3	0	120	80	85			

		3.0	HB	2	0	120	85	85			
<b>6210G3</b>	ALL	0.75	HB	4	0	120	100	100	0	6	0
		1.5	HB	2	0	120	100	100			
		3.0	HB	0	0	120	105	105			
<b>6210G4</b>	ALL	0.75	HB	4	0	115	100	100	0	6	0
		1.5	HB	2	0	115	100	100			
		3.0	HB	0	0	115	105	105			
<b>6210G5</b>	ALL	0.75	HB	4	0	115	100	100	0	6	0
		1.5	HB	2	0	115	100	100			
		3.0	HB	0	0	115	105	105			
<b>6210G6</b>	ALL	0.75	HB	2	0	115	100	105	0	6	0
		1.5	HB	1	0	115	100	105			
		3.0	HB	0	0	115	105	105			
<b>6210G7</b>	ALL	0.75	HB	3	0	105	100	105	0	6	0
		1.5	HB	1	0	105	100	105			
		3.0	HB	0	0	105	105	105			
<b>6210G8</b>	ALL	0.75	HB	3	0	105	100	105	0	6	0
		1.5	HB	1	0	105	100	105			
		3.0	HB	0	0	105	105	105			
<b>6210G9</b>	ALL	0.75	HB	3	0	105	105	105	0	6	0
		1.5	HB	1	0	105	105	105			
		3.0	HB	0	0	105	105	105			
<b>6300</b>	ALL	0.2	V-0	4	0	65	65	65	0	5	0
		3.0	V-0	1	0	65	65	65			
<b>6310</b>	ALL	0.75	V-0	3	0	120	105	105	1	7	2
		1.5	V-0	3	0	120	105	105			
		3.0	V-0	1	0	120	105	105			
<b>6400G5</b>	ALL	3.0	V-0	-	-	65	65	65	-	-	-
<b>6401G(a)</b>	ALL	3.0	V-0	-	-	65	65	65	-	-	-
<b>6401G1</b>	NC	1.5	V-1	-	-	65	65	65	-	-	-
	RD	1.5	V-2	-	-	65	65	65			
	WT, BK	1.5	V-0	-	-	65	65	65			
	ALL	3.0	V-0	-	-	65	65	65			
<b>6401G6</b>	ALL	1.5	V-0	-	-	65	65	65	-	-	-
<b>6410G(d)</b>	ALL	0.75	V-0	3	0	120	105	105	1	7	2
		1.5	V-0	3	0	120	105	105			
		3.0	V-0	1	0	120	105	105			
<b>6410G3</b>	ALL	0.75	V-0	3	0	120	105	105	1	6	2
		1.5	V-0	3	0	120	105	105			
		3.0	V-0	1	0	120	105	105			
<b>6410G4</b>	ALL	0.75	V-0	3	0	120	105	105	1	6	2
		1.5	V-0	3	0	120	105	105			

		3.0	V-0	1	0	120	105	105			
<b>6410G5</b>	ALL	0.75	V-0	0	0	130	115	120	1	6	2
		1.5	V-0	0	0	130	115	120			
		3.0	V-0	0	0	130	115	120			
<b>6512</b>	ALL	0.8	HB	-	-	65	65	65	-	-	-
		3.2	HB	-	-	65	65	65			
<b>Polybutylene Terephthalate (PBT), 30% glass reinforced, furnished as pellets.</b>											
<b>1408G6</b>	ALL	0.4-0.44	V-0	0	0	140	75	130	2	7	2
<b>Polybutylene Terephthalate (PBT), with glass fiber reinforced, furnished as pellets.</b>											
<b>140PG(m)</b>	ALL	0.75	V-0	0	0	130	75	130	4	5	1
		3.0	V-0	0	0	130	75	140			
<b>140PG3</b>	ALL	0.75	V-0	0	0	130	75	130	4	5	1
		3.0	V-0	0	0	130	75	140			
<b>140PG6</b>	ALL	0.75	V-0	0	0	130	75	130	4	5	0
		3.0	V-0	0	0	130	75	140			
<b>141PG(b)</b>	ALL	3.0-3.3	V-0	-	-	75	75	75	-	-	-
<b>Polybutylene Terephthalate (PBT), furnished as pellets.</b>											
<b>1100F, 1101FA, 1101FB, 1110F, 1111FA, 1111FB</b>											
	ALL	0.83	HB	4	1	130	75	140	0	5	0
		1.5	HB	4	0	130	120	140			
		3.0	HB	3	0	130	120	140			
		6.0	HB	1	0	130	120	140			
<b>1210G3</b>	WT, BK	0.84	HB	4	3	130	75	140	1	5	-
	ALL	1.5	HB	4	0	130	120	140			
		3.0	HB	3	0	130	120	140			
		6.0	HB	1	0	130	120	140			
<b>1210G6</b>	WT, BK	0.81	HB	2	3	140	120	140	1	5	1
	ALL	1.5	HB	1	0	140	120	140			
		3.0	HB	1	0	140	120	140			
		6.0	HB	0	0	140	120	140			
<b>1216G9</b>	ALL	0.81	HB	-	-	75	75	75	-	-	-
<b>1300</b>	ALL	0.81	V-0	4	0	105	105	105	3	6	3
		1.5	V-0	3	0	115	105	115			
		3.0	V-0	2	0	115	105	115			
		6.0	V-0	1	0	115	105	115			
<b>1300A</b>	ALL	0.75	V-0	4	0	75	75	75	3	7	2
		1.5	V-0	3	0	75	75	75			
		3.0	V-0	2	0	75	75	75			
<b>1307</b>	ALL	0.75	V-0	4	2	140	120	140	2	6	3
		1.5	V-0	4	1	140	120	140			
		3.0	V-0	2	2	140	120	140			
<b>1400G(a)</b>	ALL	0.71	V-0	4	4	130	115	120	3	6	3

		1.5	V-0	3	0	130	115	120			
		3.0	V-0	2	0	130	120	125			
		6.0	V-0	1	0	130	120	125			
<b>1400G1</b>	ALL	0.71	V-0	4	4	140	130	140	3	6	1
		1.5	V-0	3	0	140	130	140			
		3.0	V-0	2	0	140	130	140			
		6.0	V-0	1	0	140	130	140			
<b>1400G2</b>	ALL	0.71	V-0	4	4	130	115	120	3	6	3
		1.5	V-0	3	0	130	115	120			
		3.0	V-0	2	0	130	120	125			
		6.0	V-0	1	0	130	120	125			
<b>1400G3</b>	ALL	0.71	V-0	4	4	130	115	120	3	6	3
		1.5	V-0	3	0	130	115	120			
		3.0	V-0	2	0	130	120	125			
		6.0	V-0	1	0	130	120	125			
<b>1400G4</b>	ALL	0.71	V-0	4	4	130	115	120	3	6	3
		1.5	V-0	3	0	130	115	120			
		3.0	V-0	2	0	130	120	125			
		6.0	V-0	1	0	130	120	125			
<b>1400G6</b>	ALL	0.71	V-0	3	4	130	115	120	2	6	3
		1.5	V-0	2	0	130	115	120			
		3.0	V-0, 5VA	2	0	130	120	125			
		6.0	V-0	0	0	130	120	125			
<b>1401G(b)</b>	ALL	1.5	V-0	-	-	75	75	75	-	-	-
<b>1401G3</b>	ALL	1.5	V-0	-	-	75	75	75	-	-	-
<b>1401G6</b>	ALL	1.5	V-0	-	-	75	75	75	-	-	-
<b>1402G(a)</b>	ALL	0.75	V-0	4	0	140	130	140	2	6	3
		1.5	V-0	3	0	140	130	140			
		3.0	V-0	3	0	140	130	140			
<b>1402G1</b>	ALL	0.75	V-0	4	0	140	130	140	2	6	3
		1.5	V-0	3	0	140	130	140			
		3.0	V-0	3	0	140	130	140			
<b>1402G2</b>	ALL	0.75	V-0	4	0	140	130	140	2	6	3
		1.5	V-0	3	0	140	130	140			
		3.0	V-0	3	0	140	130	140			
<b>1402G3</b>	ALL	0.75	V-0	4	0	140	130	140	2	6	3
		1.5	V-0	3	0	140	130	140			
		3.0	V-0	3	0	140	130	140			
<b>1402G4</b>	ALL	0.75	V-0	4	0	140	130	140	2	6	3
		1.5	V-0	3	0	140	130	140			
		3.0	V-0	3	0	140	130	140			
<b>1402G6</b>	ALL	0.75	V-0	3	0	140	130	150	1	5	3

		1.5	V-0	2	0	140	130	150			
		3.0	V-0	1	0	140	130	150			
<b>1403G(a)</b>	ALL	0.75	V-0	4	0	130	130	140	2	6	3
		1.5	V-0	3	0	130	130	140			
		3.0	V-0	2	0	130	130	140			
<b>1403G1</b>	ALL	0.75	V-0	4	0	140	130	140	2	6	3
		1.5	V-0	3	0	140	130	140			
		3.0	V-0	2	0	140	130	140			
<b>1403G2</b>	ALL	0.75	V-0	4	0	130	130	140	2	6	3
		1.5	V-0	3	0	130	130	140			
		3.0	V-0	2	0	130	130	140			
<b>1403G3</b>	ALL	0.75	V-0	4	0	130	130	140	2	6	3
		1.5	V-0	3	0	130	130	140			
		3.0	V-0	2	0	130	130	140			
<b>1403G4</b>	ALL	0.75	V-0	4	0	130	130	140	2	6	3
		1.5	V-0	3	0	130	130	140			
		3.0	V-0	2	0	130	130	140			
<b>1403G6</b>	ALL	0.75	V-0	3	0	130	130	140	1	6	2
		1.5	V-0	2	0	130	130	140			
		3.0	V-0	2	0	130	130	140			
<b>1403G9</b>	ALL	0.75	V-0	-	-	75	75	75	-	-	-
<b>1406G6</b>	ALL	0.75	V-0	-	-	-	-	-	-	-	-
<b>1406G6A</b>	ALL	1.6	V-0	2	4	75	75	75	2	5	3
		3.0	V-0	0	4	75	75	75			
<b>140RG(b)</b>	BK	0.85	V-0	-	-	75	75	75	-	-	-
		3.2	V-0	-	-	75	75	75			
<b>1410G3</b>	ALL	3.0	V-0	-	-	75	75	75	-	-	-
<b>1410G6</b>	ALL	3.0	V-0	-	-	75	75	75	-	-	-
<b>1512</b>	ALL	0.75	HB	4	0	75	75	75	0	4	0
		3.0	HB	2	0	75	75	75			
<b>1516G9</b>	ALL	0.81	HB	-	-	75	75	75	-	-	-
<b>1519G6</b>	ALL	0.81	HB	-	-	75	75	75	-	-	-
<b>Polybutylene Terephthalate/Polycarbonate (PBT/PC), furnished as pellets.</b>											
<b>5312</b>	ALL	1.5	V-0	2	0	75	75	75	4	6	2
		3.0	V-0	1	0	75	75	75			
<b>5502</b>	ALL	1.6-1.8	HB	-	-	75	75	75	-	-	-
<b>Polycarbonate (PC), glass reinforced, furnished as pellets.</b>											
<b>5420G(N)</b>	ALL	1.5	V-0	2	0	80	80	80	4	6	3
		3.0	V-0	1	0	80	80	80			
<b>5420G2</b>	ALL	1.5	V-0	2	0	80	80	80	4	6	3
		3.0	V-0	1	0	80	80	80			
<b>5420G6</b>	ALL	1.5	V-0	1	0	80	80	80	4	6	3

		3.0	V-0	1	0	80	80	80			
<b>Polycarbonate (PC), furnished as pellets.</b>											
<b>5110</b>	ALL	1.5	V-2	3	3	120	110	125	0	5	3
		3.0	V-2	2	3	120	110	125			
<b>5210G2</b>	ALL	1.5	V-0	-	-	-	-	-	-	-	-
		3.0	V-0	-	-	-	-	-			
<b>5210G3</b>	ALL	1.5	V-0	-	-	-	-	-	-	-	-
		3.0	V-0	-	-	-	-	-			
<b>5210G4</b>	ALL	1.5	V-0	-	-	-	-	-	-	-	-
		3.0	V-0	-	-	-	-	-			
<b>5210G5</b>	ALL	1.5	V-0	-	-	-	-	-	-	-	-
		3.0	V-0	-	-	-	-	-			
<b>5210G6</b>	ALL	1.5	V-0	-	-	-	-	-	-	-	-
		3.0	V-0	-	-	-	-	-			
<b>5310</b>	ALL	1.5	V-2	3	4	120	100	115	0	5	3
		3.0	V-0	2	4	120	105	115			
<b>531P</b>	ALL	1.5-1.65	V-0	2	0	105	105	105	3	6	3
<b>540PG(e)</b>	ALL	1.5-1.65	V-0	2	0	80	80	80	3	6	3
<b>5410G(e)</b>	ALL	0.4	HB	-	-	80	80	80	4	5	3
		1.5	V-2	3	4	120	95	115			
		3.0	V-0	2	4	120	105	115			
<b>5410G1</b>	ALL	0.4	HB	-	-	80	80	80	4	5	3
		1.5	V-0	3	4	120	95	115			
		3.0	V-0	2	4	120	105	115			
<b>5410G2</b>	ALL	0.4	HB	-	-	80	80	80	4	5	3
		1.5	V-0	2	4	120	95	115			
		3.0	V-0	1	4	120	105	115			
<b>5410G3</b>	ALL	0.4	HB	-	-	80	80	80	4	5	3
		1.5	V-0	2	4	120	95	115			
		3.0	V-0	1	4	120	105	115			
<b>5410G4</b>	ALL	0.4	HB	-	-	80	80	80	4	5	3
		1.5	V-0	2	4	120	95	115			
		3.0	V-0	1	4	120	105	115			
<b>5410G5</b>	ALL	0.4	HB	-	-	80	80	80	4	5	3
		1.5	V-0	2	4	120	95	115			
		3.0	V-0	1	4	120	105	115			
<b>5410G6</b>	ALL	0.4	HB	-	-	80	80	80	0	5	3
		1.5	V-0	0	4	120	120	130			
		3.0	V-0	1	4	120	120	130			
<b>5410GE(h)</b>	ALL	1.5	V-0	-	-	80	80	80	-	-	-
<b>Polyethylene Terephthalate (PET), glass reinforced, furnished as pellets.</b>											
<b>4210G(g)</b>	ALL	1.6-1.8	HB	2	0	75	75	75	2	6	2

<b>4410G(g)</b>	BK	0.75	V-0	0	3	150	130	130	1	6	4
		1.5	V-0	0	3	150	130	130			
		3.0	V-0	0	3	150	150	150			
<b>4410G3</b>	BK	0.75	V-0	0	0	150	130	130	0	6	3
		1.5	V-0	0	0	150	130	130			
		3.0	V-0	0	0	150	150	150			
<b>4410G4</b>	BK	0.75	V-0	0	3	150	130	130	0	6	3
		1.5	V-0	0	3	150	130	130			
		3.0	V-0	0	2	150	150	150			
<b>4410G5</b>	BK	0.75	V-0	0	3	150	130	130	0	6	3
		1.5	V-0	0	3	150	130	130			
		3.0	V-0	0	2	150	150	150			
<b>4410G6</b>	ALL	0.75	V-0	0	3	150	130	130	0	6	2
		1.5	V-0	0	3	150	140	150			
		3.0	V-0	0	2	150	150	150			
<b>4410G7</b>	BK	0.75	V-0	0	3	150	130	130	1	6	4
		1.5	V-0	0	3	150	140	150			
		3.0	V-0	0	3	150	150	150			
<b>4410G8</b>	BK	0.75	V-0	0	3	150	130	130	1	6	4
		1.5	V-0	0	3	150	140	150			
		3.0	V-0	0	3	150	150	150			
<b>4410G9</b>	BK	0.75	V-0	0	3	150	140	150	1	5	4
		1.5	V-0	0	3	150	140	150			
		3.0	V-0	0	3	150	150	150			

**Polyphenylene Ether (PPE), with glass fiber reinforced, furnished as pellets.**

<b>971PG(N)</b>	WT	0.75	V-1	0	0	65	65	65	4	6	4
	NC, RD, BK	0.75	V-0	0	0	65	65	65			
	ALL	3.0	V-0	0	0	65	65	65			

**Polypropylene (PP), glass reinforced, furnished as pellets.**

<b>3219M(j)</b>	ALL	1.5	HB	-	-	110	65	110	-	-	-
		3.0	HB	-	-	110	65	110			
<b>3219M3</b>	ALL	1.5	HB	-	-	110	65	110	-	-	-
		3.0	HB	-	-	110	65	110			
<b>3219M8</b>	ALL	1.5	HB	-	-	115	65	115	-	-	-
		3.0	HB	-	-	115	65	115			

**Polypropylene (PP), furnished as pellets.**

<b>3210T(i)</b>	ALL	1.5	HB	-	-	65	65	65	-	-	-
		3.0	HB	-	-	65	65	65			
<b>3307(f1)</b>	ALL	0.8	V-0	4	0	110	110	110	0	5	0
		1.5	V-0	3	0	110	110	110			
		3.0	V-0	2	0	110	110	110			
<b>3317A</b>	ALL	0.35-0.39	V-0	-	-	65	65	65	-	-	-



<b>3410G(j)</b>	ALL	3.2-3.5	V-0	-	-	65	65	65	-	-	-
<b>Polypropylene (PP), furnished as pellets, sheets.</b>											
<b>3117(f1)</b>	ALL	1.5	HB	3	0	125	125	125	0	4	0
		3.0	HB	2	0	125	125	125			
<b>3210G(e)</b>	ALL	0.75	HB	4	3	65	65	65	0	6	0
		1.5	HB	3	1	65	65	65			
		3.0	HB	2	0	65	65	65			
<b>3210G4</b>	ALL	0.75	HB	3	3	65	65	65	0	6	0
		1.5	HB	3	0	65	65	65			
		3.0	HB	2	0	65	65	65			
<b>3210G5</b>	ALL	0.75	HB	3	3	65	65	65	0	6	0
		1.5	HB	3	0	65	65	65			
		3.0	HB	2	0	65	65	65			
<b>3210G6</b>	ALL	0.75	HB	2	3	65	65	65	0	5	0
		1.5	HB	1	0	65	65	65			
		3.0	HB	0	0	65	65	65			
<b>3310</b>	ALL	0.75	V-2	4	0	110	65	65	0	4	0
		1.5-1.7	V-2	4	0	110	110	110			
<b>3317(f1)</b>	ALL	0.75	V-0	4	2	115	115	115	0	6	0
		1.5	V-0	3	1	115	115	115			
		3.0	V-0	2	0	115	115	115			
<b>3410T8</b>	ALL	0.8	V-2	-	-	65	65	65	-	-	-
		1.6	V-2	-	-	65	65	65			
		3.1	V-2	-	-	65	65	65			
<b>Polypropylene (PP), furnished as pellets,sheets.</b>											
<b>3210G1</b>	ALL	0.75	HB	4	3	65	65	65	0	6	0
		1.5	HB	3	1	65	65	65			
		3.0	HB	2	0	65	65	65			

(a) - May be followed by a number 1-6 indicating glass-fiber content between 5-30%

(b) - May be followed by a number or letter indicating glass fiber content 15-30%

(c) - May be followed by a letter indicating glass fiber content 1-45%

(d) - May be followed by a letter indicating glass fiber content 1-25%.

(e) - May be followed by a letter between 1-6 indicating glass-fibercontent between 1-30%

(f1) - Suitable for outdoor use with respect to exposure to Ultraviolet Light, Water Exposure and Immersion in accordance with UL 746C.

(f2) - Subjected to one or more of the following tests: Ultraviolet Light, Water Exposure or Immersion in accordance with UL 746C, where the acceptability for outdoor use is to be determined by UL  
 Subjected to one or more of the following tests: Ultraviolet Light, Water Exposure or Immersion in accordance with UL 746C, where the acceptability for outdoor use is to be determined by UL.

(g) - May be followed by a number 3 - 9 indicating glass-fiber content between 15 - 45%

(h) - May be followed by a letter indicating glass fiber content 1-50%

(i) - May be followed by a number between 2-8 indicating Talcum power contest 10-40%

(j) - May be followed by a number between 3-8 indicating glass fiber contest 15-40%.

(k) - May be followed by a letter indicating glass fiber content between 5~40%

(m) - May be followed by a letter or number indicating glass fiber content between 15 and 30 percent, except 15% and 30%

(N) - May be followed by a letter indicating glass-fiber content between 10~30%

Marking: Company name and material designation on container, wrapper or finished part.

Last Updated on 2016-01-21

---

[Questions?](#)

[Print this page](#)

[Terms of Use](#)

[Page Top](#)

© 2016 UL LLC

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2016 UL LLC".